

Jon S. Corzine

State of New Jersey Department of Community Affairs Division of Codes and Standards PO Box 802 Trenton, New Jersey 08625-0802



Susan Bass Levin Commissioner

June 1999 Date:

Code Ref. Update: August 2006 Subject:

Permissible Penetrations

in Roof Assemblies for

Residential Groups

References: N.J.A.C. 5:23-3.14,

Building Subcode, Section 705.6, Exception #6

The language of Section 705.6, Exception 6 in the Building Subcode has led to confusion in the application of the third condition of that exception. Condition 6.3 of Section 705.6 prohibits openings within four feet of a firewall in residential groups.

This section was intended to prohibit skylights, ridge vents, or mechanical and passive exhaust termination points within four feet of a firewall; it was not intended to apply to chimneys and plumbing stacks. Therefore, for the purpose of applying this section, chimneys, plumbing stacks, and electrical service masts are not to be considered prohibited openings, and are permitted to be located within four feet of the firewall. All permssible penetrations shall be sealed at the roof line.

> William M. Connolly Director Division of Codes and Standards

PURSUANT TO THE AUTHORITY OF N.J.S.A. 52:27D-119 ET SEQ., AS AMENDED, THE ABOVE FORMAL TECHNICAL OPINION IS CON-SIDERED TO BE BINDING UPON ALL CODE OFFICIALS.

##